

DESCRIPTION

New thin, flexible 60W USB-C power supplies provide up to 20V at 3A

APPLICATION

Mobile Phones, Tablets, Automotive convenience ports, TV, Mass Storage, Expansion Ports, Laptops, Monitors, Payment terminal, Set-top boxes, Workstations

FEATURES

- AC Input 100 to 240v AC, at 2A 47-63 Hz
- Wide range of output voltages, up to 20v at 3A
- Able to power devices up to 60 watts
- The thinnest C14 adapter available today, only 92 x 77.3 x 25.4mm
- Includes ground wire for safety
- High power output density of up to 6.01 W/in³
- Meets DoE level 6 standard for energy efficiency
- C14 and C6 AC socket versions available
- Full thermal and electrical safety protection
- Elegant, simple, compact design
- There are five different output voltage (5v, 9v, 12v, 15v, 20v)

WATTAGE

Wattage: 60W

PRODUCT HIGHLIGHT

V-Output: 5, 9, 12, 15, 20
O/P Current: 3A
Socket Type: C14

INPUT ELECTRICAL

Input Voltage: 100 ~ 240 V
Input Frequency: 47 ~ 63 Hz
Input Current: 2A

OUTPUT ELECTRICAL

Single Output: 5 V/ 3 A
Second Output: 9V/ 3A
Third Output: 12V/ 3A
Fourth Output: 15V/ 3A
Output Accuracy: +/- 5%
Line Regulation: +/- 5%
Load Regulation: +/- 5%

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice



SAFETY STANDARD APPROVAL



NO LOAD AND EFFICIENCY

No Load: 0.21 Watts
Efficiency: 88 %

PROTECTION

Protection: OVP, OCP, OTP, OPP

ENVIRONMENTAL REQUIREMENTS

MTBF: 300,000Hrs Min. Telcordia SR-332
Issue2 (25°C)

MECHANICAL

Dimension: 92mm(L) x 77.3mm(W) x 25.4mm(H)
LED Indicator: No
On/ Off Switch: No